

SAGE SRL SPECIFICATIONS

REMOTE STYLE GENERAL PURPOSE BLIND INSERTION MASS FLOWMETER

Flow Meter is thermal dispersion type, utilizing constant temperature difference method of measuring Gas Mass Flow Rate. It contains two reference grade platinum RTD sensors clad in a protective 316 SS sheath. Features direct Mass Flow for gases, wide rangeability, low pressure drop, very low end sensitivity, and no moving parts.

Flow Meter is microprocessor based, does not have any potentiometers, and has RS232 communications that is accessible with optional cable assembly. Flow Meter is powered by 24 VDC or 115 VAC/ 230 VAC. The power dissipation is under 6 watts (e.g. under 250 ma at 24 VDC).

Electronics is Remote Style, with NEMA 4X Blind Enclosure. The electronics has a 4 to 20 ma opto-isolated output proportional to Mass Flow Rate as well as a 0 to 5 VDC output proportional to Temperature. Optionally, the 0 -5 VDC output can be configured to provide pulsed outputs of Totalized Flow (other output will be disabled).

The Flow Element is an Insertion Style, consisting of a 1/2" OD probe (3/4" optional) with lengths up to 36" long (typically 15" long) suitable for insertion into the center of a process pipe. Mounting hardware choices (such as Isolation Valve Assemblies, Compression Fittings, and Flange Mounts) are optionally available.

Flow Element's Junction Box is Explosion Proof (Class 1, Div 1, Groups B, C, D), and does not have any electronics – only a wiring terminal block. The Flow Element will be connected to the Electronics by 25 feet of lead-length compensated cable. The cable (6-conductor) can be lengthened or shortened without affecting accuracy (max loop resistance 10 ohms, over 1000 feet).

Accuracy is +/- 0.5% of Full Scale +/- 1% of Reading with a turn-down of up to 1000 to 1. Repeatability shall be 0.2%. The Flow Meter is Sage Metering, Inc. SRL Series.

